K-Dee II King Single







Lightweight and versatile like our standard K-Dee II beds, with the added comfort of a King Single bed.

Product Specs

K-Dee II King Single

Safe working load: 213KG
Overall length: 2270mm
Overall width: 1160mm
Overall height: 830-1220mm
Mattress platform length: 1900mm
Mattress platform width: 1050mm
With added length extension: 2100mm

Head down tilt: 0-11° Foot down tilt: 0-11° Head/foot width: 980mm

Mattress platform height: 335-725mm Underbed clearance: to frame 295mm Underbed clearance min: 145mm

Back adjustment: 0-70 ° Knee break adjustment: 0-23 ° Leg rest adjustment: -27-0 ° **Order code: B09-KDII-KS**

Features

- Can be fully disassembled for transport, and stored in a secured position with transport stand
- Handset with nurse lockout function
- Trendelenburg and reverse trendelenburg functionality
- 4-section power adjustable bed
- Optional 200mm length extension
- · Height, backrest and knee break powered adjustment
- Powered tilt adjustment
- Individual locking PU castors with steel brackets
- Open bed ends with beech woodgrain panel
- E1 and Class 3 Fire Retardant
- Tested to BS EN 60601-1:2006 and BS EN 60601-2-252:2010 saftey standards
- Dewert actuators
- AkzoNobel Powdercoat
- Optional rails: full length steel, full length wooden, or 3/4 rails
- Optional accessories: self help pole, IV pole, clamp rail, padded rail covers, mattress bolsters

K-Dee Classic King Single

Safe working load: 213KG
Overall length: 2270mm
Overall width: 1160mm
Overall height: 830-1220mm
Mattress platform length: 1900mm
Mattress platform width: 1050mm
With added length extension: 2100mm

Head down tilt: 0-11°
Foot down tilt: 0-11°
Head/foot width: 980mm

Mattress platform height: 335-725mm Underbed clearance: to frame 295mm Underbed clearance min: 145mm Back adjustment: 0-70°

Knee break adjustment: 0-23° Leg rest adjustment: -27-0°

Order code: BO8-KD-CLASSIC-KS

Features

- Can be fully disassembled for transport, and stored in a secured position with transport stand
- Handset with nurse lockout function
- Trendelenburg and reverse trendelenburg functionality
- 4-section power adjustable bed
- Optional 200mm length extension
- Height, backrest and knee break powered adjustment
- Powered tilt adjustment
- Individual locking enclosed plastic castors
- Enclosed Wooden bed ends in Beech woodgain
- E1 and Class 3 Fire Retardant
- Tested to BS EN 60601-1:2006 and BS EN 60601-2-252:2010 saftey standards
- · Dewert actuators
- AkzoNobel Powdercoat
- Optional rails: full length steel, full length wooden, or 3/4 rails
- Optional accessories: self help pole, IV pole, clamp rail, padded rail covers, mattress bolsters